

*Leveraging the experience and reliability of the world's leading convenience deployment brand, Nautilus Hyosung - the Monimax 5600 offers complete deployment flexibility and a broad range of non-traditional service offerings. Ideal for in-branch or off-premise deployments, the 5600 is a superior option when reliability, security, and high capacity are required.*

## **Features**

### **Superior, Flexible Design**

The 5600 boasts one of the most efficient user interfaces available - 10% to 40% more compact than most competitors. The 5600 also offers a full range of advertising and marketing support along with a five high option for the dispenser. An industry standard 15.1" TFT may be complimented with an optional, unique vacuum fluorescent display (VFD) for unparalleled visibility.

### **Security**

The 5600's UL-291 Level 1 rated safe has been proven in the field time and again, with independent third party attack tests revealing the ability of the Nautilus Hyosung enclosure to withstand attacks more severe and over a longer period of time than the UL rating requires. Additionally, market leading software and transactional security features are available as options, as are video surveillance cameras.

### **Dependability**

Reliability derived from being the market leader in cash dispensing technology, and availability provided by high capacity modules, the 5600 is the ideal self-service platform for transaction intensive branch or off premise deployments.

Monimax 5600 is designed with speed in mind. Rapid transaction processing to cardholders, speedy service events enhanced by access by design, and quick deployments enabled by platform flexibility. All in one highly secure, reliable platform.



**Hyosung - Always By Your Side. Nautilus Hyosung is more than reliable, proven self service technology. We are a company dedicated to the success of our partners.**

# MONIMAX 5600

## System Control

- Intel® processor
- Microsoft® Windows® XP platform
- NDC+, User Application

## Communication

- TCP/IP

## Customer Display

- 15" color TFT LCD
- Sunlight readable w/touch screen

### Optional

- Privacy filter
- Touch screen

## Input Type

- 4x2 function keys (option)
- PCI EPP (Encrypting PIN Pad)
- ADA compliant

## Card Handling

- Dip-type card reader

### Optional

- Anti-skimming

## Cash Dispensing

- 3,000 notes cassette  
(Up to 5 cassettes)
- Bundle retraction
- Automatic shutter

## Printers

- 3.1" graphical thermal receipt printer
- Electronic journal
- 5,000 transactions

## Security

- UL291 Level 1 safe
- Electronic safe lock

### Optional

- KABA Mas Cencon safe lock
- Security camera

## Miscellaneous

- Lead-through indicator

### Optional

- VFD (Vacuum Fluorescent Display)

## Power Supply

- AC 110 – 240V, 50–60Hz
- Backup battery

## Operating Environment

- Temperature: 31°F – 104°F ( 0°C – 40°C)

### Optional

- Humidity: 25%–85%

## Dimension and Weight

- Height : 59.3" (1,505 mm)
- Width : 18.5" (470 mm)
- Depth : 29.9" (760 mm)
- Weight : 1093 lbs (495 kg) (Level 1 Safe)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



 NAUTILUS HYOSUNG

NH 5600  
001\_06/2011

Contact your authorized Nautilus Hyosung distributor or representative for more information.